

ADC Structured Cabling Solutions

Category 5e UTP Cable

Issue 2



This Category 5e UTP 4-pair Cable is an unshielded cable, designed to provide Category 5e Enhanced Link and Channel performance with internationally defined physical and electrical performance up to 100MHz.

The insulation on the 4 pairs for twisted copper is colour coded: Blue, Orange, Green, and Brown.

Specifications

Conductor:0.5mm Dia. (24 AWG) copper
Insulation:Polyethylene
Jacket:PVC
Outside diameter:5.0 mm nominal
Complies with : ISO/IEC 11801
 TIA/EIA 568-B.2
 IEC60332.1

Mechanical:

Minimum bending radius:
- During installation50mm
- After installation.....25mm
Maximum pulling tension:108N (11kg)
Box mass, full, nominal:11kg

Thermal:

Operation:-15°C to 70°C
Installation:5°C to 40°C
Flame rating:CM

Electrical:

Conductor DC resistance @ 20°C (max):9.38Ω/100m
DC resistance unbalances (max):5%
Mutual capacitance @ 20°C (max):5.6nF/100m
Worst case cable skew.....45ns/100m
NVP setting.....70%

SPEC SHEET



www.adc.com/in • 1800 425 8232

ADC Structured Cabling Solutions

Category 5e UTP Cable

Operating voltage (max):300Vdc

Freq	Attenuation	Pr-Pr NEXT	Power Sum NEXT	Return Loss	Pr-Pr ELFEXT	Power Sum ELFEXT	Pr-Pr ACR	Power Sum ACR
(MHz)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)
1.00	1.95	77.2	77.0	31.5	74.7	76.9	75.2	75.0
4.00	3.62	71.0	68.7	28.7	64.7	64.7	67.4	65.1
10.00	6.11	61.4	61.8	32.1	55.9	55.7	55.3	55.6
16.00	7.89	60.4	66.3	32.1	51.7	51.7	52.5	58.4
20.00	8.77	55.5	64.8	28.9	50.0	49.7	46.7	56.1
31.25	11.09	52.4	53.8	28.8	46.1	45.1	41.3	42.7
62.50	15.96	52.4	52.4	25.2	39.1	38.9	36.5	36.5
100.00	20.41	47.0	46.2	26.8	31.8	34.2	26.6	25.8
200.00	29.73	39.1	41.8	19.1	25.1	28.8	9.4	12.0
250.00	33.53	38.4	42.6	19.3	25.3	31.1	4.9	9.1
300.00	36.74	36.1	34.8	16.9	18.9	18.3	-0.7	-2.0
350.00	39.89	32.3	33.0	15.8	17.7	15.8	-7.6	-6.9

Note: The above listed discrete frequency performance values are provided for engineering information only. Actual compliance testing is based on swept frequency measurements. The spec values are based on TIA.EIA 568-B.2 specifications.

Ordering Information

Description	Quantity	Colour	Product No.
Category 5e 4-pair Cable, Solid UTP	305m reel	Grey	6499 1 028-01
Category 5e 4-pair Cable, Solid UTP	305m reel	Blue	6499 1 028-02

*KRONE Communications Ltd. is now ADC India Communications Ltd.

SPEC SHEET



www.adc.com/in

10C, II Phase Peenya Industrial Area
Bangalore 560 058
Sales Support: 1800 425 8232

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6499 1 028-XXIN / Issue 2 © 2010 ADC Telecommunications, Inc. All Rights Reserved.