

# ADC Structured Cabling Solutions

## Category 5e Patch Panels

Issue 2



24-port enhanced patch panel A/B

ADC's Category 5e patch panels are an integral part of ADC Structured Cabling system and provide Category 5e performance in a high-density design with concise station and port labeling. Available in 24 and 48 port variants, all ADC Structured Cabling patch panels feature LSA-PLUS® silver-plated 45° angled contacts for the most reliable and robust connection available.

### Features:

- UL 1863 listed and Category 5e performance verified
- Includes rear wire manager
- Wire can be terminated with either a ADC or 110 tool
- Forty-five degree silver-plated IDCs provide secure, reliable gas-tight connection
- Includes paper labels or silk-screened area for station identification
- Universal wiring label for easy termination of either T568A/B
- Designed for Gigabit Ethernet transmission
- Panels can be rack mounted in standard EIA 19-inch racks or wall mounted using optional 19-inch hinged wall-mount brackets

### Specifications

Environment for Use: .....	Indoors, in dry, closed room
Operating Temperature Range: .....	-40° to 70 °C (-40° to 158 °F)
Maximum Relative Humidity: .....	< 90% non-condensing
RJ Socket, 8 Positions, General Specification: .....	FCC Part 68.500, IEC 60603-7, EN 60603-7
Transmission Performance and Reliability:	
TIA/EIA 568-B.2 Category 5e	
ISO 11801 Class D Standard	
EN 50173 Category 5e	
Number of Plug Insertion Cycles: .....	> 750
LSA-PLUS® Insulation Displacement	
Wire Diameter Range for Solid and .....	22-26 AWG
Stranded Copper Conductors: .....	0.40 mm to 0.65 mm (0.016" to 0.025")
Wire Insulation Diameter Range (PE,PVC): .....	0.70 mm to 1.70 mm (0.028" to 0.067")
RJ Interface Resistance: .....	< 20 mΩ

SPEC SHEET



[www.adc.com/in](http://www.adc.com/in) • 1800 425 8232

# ADC Structured Cabling Solutions

## Category 5e Patch Panels

LSA-PLUS® Contact Resistance: ..... < 1 mΩ  
 Contact Re-terminations ADC Tool: ..... > 200  
 Insulation Resistance at 40 °C (104 °F) and 93% RH:..... > 500 MΩ  
 Electrical Rating of Complete Assembly at 25 °C (77 °F) and 50% RH  
     Ringing Voltage Rating: ..... < 150V AC  
     Insulation Resistance:..... > 100 MΩ at 500 VDC  
 Safety Rating: ..... UL 1863  
 Flammability Rating:..... UL 94 V-0

### Ordering Information

Description	Dimensions(HxWxD)	Product No.
<b>24-port patch panel with snap-in port ID tabs and paper labels,</b> T568A/B compatible	44.45 mm x 482.6 mm x 38.1 mm (1.75" x 19" x 1.5")	6653 1 587-24
<b>48-port patch panel with snap-in port ID tabs and paper labels,</b> T568A/B compatible	88.9 mm x 482.6 mm x 38.1 mm (3.5" x 19" x 1.5")	6653 1 587-48

SPEC SHEET

\*KRONE Communications Ltd. is now ADC India Communications Ltd.



**www.adc.com/in**

10C, II Phase Peenya Industrial Area  
 Bangalore 560 058  
 Sales Support: 1800 425 8232

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101  
 Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

**6653 1 587-XXIN / Issue 2 © 2010 ADC Telecommunications, Inc. All Rights Reserved.**